



Maria Anna Cusenza \*, Maurizio Cellura, Francesco Guarino and Sonia Longo 💿

Department of Engineering, University of Palermo, Viale delle Scienze Ed.9, 90128 Palermo, Italy; maurizio.cellura@unipa.it (M.C.); Francesco.guarino@unipa.it (F.G.); sonia.longo@unipa.it (S.L.) \* Correspondence: mariaanna.cusenza@unipa.it

**Abstract**: This study assesses the potential environmental impacts related to the energy valorization of agro-food industry waste thought the Life Cycle Assessment methodology (ISO 14040). The system examined consists of a real anaerobic digester coupled with a combined anaerobic digester and heat and power plant (AD-CHP) operating in Sicily. The analysis accounts for all the impacts occurring from the delivery of the biomass to the AD-CHP plant up to the electricity generation in the CHP. The main outcomes of the study include the eco-profile of the energy system providing electricity and the assessment of the contribution of each life cycle phase aimed at identifying the potential improvement area. The obtained results highlight that the direct emissions associated with the biogas combustion process in the CHP account for 66% of the impact on climate change, and feedstock transport contributes 64% to the impact on mineral, fossil fuels, and renewable depletion. The contribution to the impacts caused by the electricity consumption is relevant in many of the environmental categories examined. It ranges from a minimum of about 22% for climate change up to 82% for freshwater ecotoxicity. Then actions aimed at reducing electricity consumption can significantly improve the environmental performances of the energy system examined.

Keywords: residual biomass; energy valorization; life cycle assessment; environmental sustainability

# 1. Introduction

The energy valorization of biomass (bioenergy) has been recognized as an effective solution to improve the security and the environmental sustainability of the European Union's energy supply [1] and to achieve the EU's renewable energy targets for 2030 and beyond [2].

Besides energy crops specifically grown for the production of biomass for energy uses (rapeseed, corn, sorghum, etc.), an alternative source of biomass is represented by bio-wastes and residues, like slurry and manure from livestock farming, as well as waste such as olive pomace, vegetable residues, slaughter residues, and fruit processing wastes from the agri-food transformation industry.

The residual biomasses are particularly interesting as an economic and sustainable biomass source. The production of energy from bioenergy crops can present various environmental issues [3–5]. For example, bioenergy crops can have a significant impact due to the need for intensive agricultural practices that involve the use of fertilizers and pesticides, the consumption of a large amount of water, etc. In addition, growing bioenergy crops in an irrigated agriculture area may also result in increased competition for land and water resources with impacts on local food security of the Food and Agriculture Organization of the United Nations (FAO) [6]. In this context, residual biomasses are acquiring a key role in bioenergy production.

The energy valorization of biomasses through an anaerobic digestion process (AD) transforms the organic substance into biogas, a mixture consisting of 50-70% methane (CH<sub>4</sub>), and for the remaining part, carbon dioxide (CO<sub>2</sub>) and other components (hydrogen sulfide, ammonia, and hydrogen) [7].



Citation: Cusenza, M.A.; Cellura, M.; Guarino, F.; Longo, S. Life Cycle Environmental Assessment of Energy Valorization of the Residual Agro-Food Industry. *Energies* **2021**, *14*, 5491. https://doi.org/10.3390/en14175491

Academic Editor: Alberto-Jesus Perea-Moreno

Received: 30 July 2021 Accepted: 30 August 2021 Published: 2 September 2021

**Publisher's Note:** MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



**Copyright:** © 2021 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https:// creativecommons.org/licenses/by/ 4.0/).



The biogas produced in the anaerobic digester, after a purification treatment, can be used for the generation of electrical or thermal energy, or for the simultaneous generation of both forms of energy in cogeneration plants (CHP). Moreover, the upgrade of biogas increases the concentration of  $CH_4$  in the mixture allowing one to obtain a gas with similar characteristics to natural gas (biomethane) compatible with the injection to the national gas grid [8–10].

Although the energy valorization of residual biomasses avoids the land and chemicals use issues associated with energy crops [11], other environmental issues are related to the biomass transport, and the operation phase of the AD and power plants requires deeper analysis of the environmental performance of these energy systems.

In order to assess the environmental impacts of biomass energy valorization chains, the Life Cycle Assessment (LCA) methodology has been applied in Europe and worldwide since it is widely recognized as the best framework for assessing the potential environmental impacts of products, processes, and systems [12–15]. LCA is a methodology based on a scientific approach, internationally standardized by the standards of the series ISO 14040 [16,17]. LCA allows for estimating the energy and environmental performance during the entire life cycle of a system under examination.

Two extensive literature reviews on LCA applied to energy valorization of the biomass supply chain have been carried out by Fantin et al. [18] and Bacenetti et al. [12]. The reviews highlighted that:

- Few studies model foreground processes using only primary data (such as [19–23]); in fact, most of them are mainly based on data from field reports and studies often integrated with data taken from environmental databases (such as [24–27]).
- Most of the studies reviewed focus on a CHP plant size of 500 kW and few below 100 kW;
- Most of them consider a limited number of impact categories (such as [20,28–30]).

In this context, the authors perform an LCA study in order to estimate the environmental impacts of the electricity generation in a real anaerobic digestion–combined heat and power plant (AD–CHP) and to identify the environmental hotspots. The AD is fueled with residual biomasses from the agro-industry sector and the produced biogas is injected in a 100 kW CHP.

In relation to the literature examined, the analysis is carried out by using mainly primary data collected by means of questionnaires and interviews with the plant owners and operators. The plant is modeled considering the real operating conditions. In addition, some strategies for improving the operating conditions are investigated in order to highlight the potential environmental benefits that can be obtained. Finally, a wide range of environmental impact categories are investigated.

The obtained results can represent a useful support for policy makers in the strategic planning of bio-waste management systems [23,31] and for the agro-industry sector stakeholders in the introduction of new technologies for bio-waste management and marketing purposes.

# 2. Materials and Methods: Life Cycle Assessment

The authors apply an attributional LCA approach in compliance with the international standards of series ISO 14040 [16,17]. The attributional LCA is based on a life cycle inventory (LCI) frame that inventories the input and output flows of all processes of the system examined as they occur [32].

- The LCA methodology operates with four separate phases [16,17]: Goal and scope definition. The goal sets the decision context and the intended application of the study. During the scope definition, the object of the LCA study is identified and described in detail and all methodological aspects of the LCA study are set (such as functional unit, system boundaries, data quality, etc.);
- 2. Life cycle inventory (LCI). During this phase, information about the physical flows in terms of input of resources, materials, products, and the output of emissions, waste, and valuable products for the product system are collected. The result of the PCI

phase is the inventory table that lists the inputs and the outputs of elementary flows of the product system;

- 3. Life cycle impact assessment (LCIA). In this phase, the elementary flows that have been assessed in the inventory analysis are translated into impacts on the environment;
- 4. Life cycle interpretation. In this phase, the findings of either the LCI or LCIA are evaluated in relation to the defined goal and scope in order to reach conclusions and recommendations.

# 2.1. Goal and Scope Definition

The main goals of the study are:

- To estimate the potential environmental impacts and benefits related to the energy valorization of residual biomass derived from the agro-food industry through an anaerobic digester (AD)–combined heat and power plant (CHP) system (AD–CHP);
- To assess the contribution of each life cycle phase to the overall impacts.

The examined AD-CHP is a real system operating in Sicily (Italy) since 2016. The average operational time is 7920 h per year (330 days per year). The anaerobic digestion occurs in a continuous stirred-tank reactor through a single-stage process and under mesophilic conditions (40 °C). The plant utilizes several residual biomasses available in situ and at short-to-medium distance. The feedstocks are pre-mixed in a feeding tank in order to obtain a homogeneous mixture entering the AD. In the AD, the feedstock is mechanically mixed, and it is heated through a heat exchanger that recovers the thermal energy generated by the CHP. The outputs of the anaerobic digestion process are biogas and digestate (that can be used as fertilizer [33]). The volume of digestate is around 90–95% of that fed into the digester.

The biogas produced is stored in the gasholder dome placed on the top of the digester. Before being fed into the CHP, the biogas is desulfurized, filtered, and dehumidified in a chiller. The purified biogas is fed into the CHP to generate electrical and thermal energy. The electricity generated is partially fed into the national grid and partially used by the product system investigated. The heat is partially recirculated to fulfil the requirement of the digester and the surplus is wasted into the atmosphere.

The main technical characteristics of the AD and CHP plants are recapped in Table 1.

| AD Parameter                 | Value   |
|------------------------------|---------|
| Net volume (m <sup>3</sup> ) | 1300 *  |
| CHP parameter                | Value   |
| Electric power (kW)          | 100 **  |
| Electrical efficiency (%)    | 37.3 ** |
| Thermal power (kW)           | 138 **  |
| Thermal efficiency (%)       | 51.5 ** |

Table 1. Main technical characteristics of the AD and CHP plants.

\* Plant owner's data; \*\* CHP data sheet available at www.mtmenergia.com (accessed on 25 August 2021).

The functional unit (FU) is 1 kWh of electricity generated by the energy system under investigation. The system boundaries include the transport of the feedstocks that are not locally available to the plant; the "sulla" silage production; the anaerobic digestion process; the combustion of biogas in the CHP unit, and the production processes of the materials employed in the infrastructures. The flow chart of the examined energy system and the unit processes included within system boundaries are illustrated in Figure 1.





The environmental burdens are entirely allocated to electrical energy as the surplus thermal energy and the digestate are discharged as waste [34].

The production processes of olive pomace, whey, citrus processing waste, chicken, and bovine manure are not included within the system boundaries. In fact, since they are the waste of other production processes, a zero-burden approach is assumed and then only the impact related to their transportation is accounted for in the examined system [22]. Concerning "sulla", it is assumed that it grows spontaneously, and only the impact related to the silage production process is considered.

Other assumptions concern the AD and CHP lifetimes. The useful lifetime of the AD plant is assumed to be 20 years [34,35], while for the CHP plant, a lifetime of 10 years is assumed [34].

The impact assessment is based on the ILCD 2011 midpoint method and impact categories recommended by the European Commission [36]. The selected impact categories are listed in Table 2.

Impact Category Acronym Global Warming Potential (kgCO<sub>2eq</sub>) GWP ODP Ozone Depletion potential (kgCFC-11<sub>eq</sub>) HT-nce Human toxicity-cancer effect (CTUh) Human toxicity-cancer effect (CTUh) HT-ce Particulate Matter (kg PM2.5<sub>eq</sub>) PM Ionizing Radiation-human health (kBqU<sup>235</sup>eq) IR-hh Ionizing Radiation-ecosystem (CTUe) IR-e Photochemical Ozone Formation Potential (kgNMVOCeq) POFP Acidification Potential (molH<sup>+</sup>eq) AP Terrestrial Eutrophication (molNeq) EUT Freshwater Eutrophication (kgPeq) EUF Marina Eutrophication (kgNeq) EUM Freshwater Ecotoxicity (CTUe) E<sub>FW</sub> Land use (kg C<sub>deficit</sub>) LU Water resource depletion (m<sup>3</sup><sub>water</sub>) WRD Mineral Fossil and Renewable Resource Depletion (kgSb<sub>eq</sub>) MFRRD

| Table | e 2. | Impact categories. |
|-------|------|--------------------|
|-------|------|--------------------|

To evaluate how the methodological choices relate to the multifunctionality management, the impact assessment method, and the uncertainty of the LCI data, and how this affects the life cycle impact assessment results, a sensitivity analysis is carried out. Concerning the multifunctionality management, the substitution approach by system expansion is applied according to the ISO 14044 hierarchy. In detail, it is hypothesized that the surplus of thermal energy can be used, avoiding the production of an equivalent amount of thermal energy from an alternative energy system producing thermal energy. Concerning the digestate, it is assumed that it can be used as fertilizer, avoiding the production of a functional equivalent amount of mineral fertilizer. Moreover, to assess how the impact assessment method affects the results of the LCA, further evaluation is carried out applying the EF 3.0 method (adapted) developed within the environmental footprint initiative [37]. Finally, Monte Carlo simulation is applied to estimate the uncertainties in the LCIA results introduced by the statistical variability or temporal, geographical, or technological gaps in the LCI data [38–40]. Moreover, a sensitivity analysis is carried out to assess how the most contributing processes affect the obtained results, increasing/decreasing the related values by 30%.

# 2.2. Life Cycle Inventory (LCI) Analysis

The following paragraphs illustrate data collection and elaboration for obtaining the inventory of the examined system. The energy system is modelled by using primary data collected via questionnaires and interviews with the plant managers and operators and through assumption based on the scientific literature in this area. In addition, secondary data from the Ecoinvent 3.6 database are employed [35] for modelling materials and energy sources (background processes) used in the examined energy system. The recycled content, or cut-off, approach is used to compile the LCI.

Unless otherwise specified, the system's energy consumption is estimated based on the rated power and the operation hours declared by the plant managers and operators. It is assumed that the electrical energy required for plant operation is partially satisfied by the CHP plant. The remaining electricity requirements are satisfied by purchasing electricity from the grid. According to the literature, it is assumed that a percentage equal to 8% of the electricity generated by the CHP is consumed within the product system [22,41].

#### 2.2.1. Feedstock Supply

The feedstocks employed consist of olive pomace, whey, chicken manure, citrus processing waste, bovine manure, and "sulla" (Hedysarum coronarium) silage. The unit process "feedstock supply" involves the "sulla" silage production, the mixing process, and the mixing tank construction.

According to the recycled content approach, only the burdens associated with the sulla ensiling and to the residual biomass transportation processes are considered within the feedstock supply life cycle phase.

The "sulla" silage production is modelled according to Bacenetti and Fusi [42] assuming maize silage production as a proxy for "sulla" silage production. The feedstocks not locally available are transported to the plant by truck. The construction process of the mixing tank is modelled based on the technical design report of the plant. The useful lifetime of the mixing tank is assumed to be 20 years. Within the mixing tank, the feedstock is homogenized through a 11 kW mechanical stirrer operating 20 h/day.

Table 3 shows the types of substrates used in the AD plant and the transport distance for each feedstock. These data are based on plant owner's primary data.

# 2.2.2. Anaerobic Digestion

The anaerobic digestion unit process involves the anaerobic digestion plant and the necessary treatments before feeding the biogas into the CHP.

The feedstock is fed into the AD by means of a centrifugal pump. The daily biomass entering the digester is about 17 tons (Table 4). The biomass within the AD is mixed by

3 mechanical stirrers. Two have a rated power of 9 kW and work 20 h/day, while one has a rated power of 11 kW and works 4 h/day.

 Table 3. Feedstock supply.

| Feedstock                           | Amount (ton/Day) | Transport Distance (km) |
|-------------------------------------|------------------|-------------------------|
| Olive pomace                        | 0.7              | 25                      |
| Whey                                | 8.4              | 60                      |
| Chicken manure                      | 1.9              | 100                     |
| Citrus processing waste             | 4.0              | 200                     |
| Bovine manure                       | 0.9              | Local                   |
| Sulla (Hedysarum coronarium) silage | 1                | Local                   |

**Table 4.** Data collection and elaboration results.

| Life Cycle Phase                             | Amount               | Type of Data  | Ecoinvent 3.6 Dataset Selected<br>for LCI Modelling               |  |
|--|----------------------|---|---|--|
| Feedstock supply                             |                      |   |   |  |
| Feedstock (t/d)                              | $1.7 	imes 10^1$     | Own calculations based on plant<br>owner's data                     | Burden free   |  |
| Sulla ensiled                                | $1.0	imes10^{0}$     | Literature data [42]  | (See Table 3)   |  |
| Transport (tkm/d)                            | $1.5	imes10^3$       | Own calculations based on plant<br>owner's data                     | Transport, freight, lorry<br>16–32 metric ton (EURO 6)            |  |
| Operational phase                            |                      |   |   |  |
| Electricity-mixing tank (kWh/d)              | $2.2 \times 10^2$    | Own calculations based on plant<br>owner's data                     | 92% Electricity low voltage (IT),<br>8% self-consumption from CHP |  |
| Electricity-AD (kWh/d)                       | $5.2 	imes 10^2$     | Own calculations based on plant<br>owner's data                     | 92% Electricity low voltage (IT),<br>8% self-consumption from CHP |  |
| Electricity-Biogas treatment (kWh/d)         | $1.2 	imes 10^2$     | Own calculations based on plant<br>owner's data                     | 92% Electricity low voltage (IT),<br>8% self-consumption from CHP |  |
| Electricity–CHP (kWh/d)                      | $3.6 	imes 10^1$     | Own calculations based on plant<br>owner's data                     | 100% Electricity low voltage (IT)                                 |  |
| Thermal energy-CHP (kWh/d)                   | $8.8\times10^{2a}$   | Own calculations based on plant<br>owner's data                     | Self-consumption (AD process)                                     |  |
| Lubricant oil-CHP (kg/d)                     | $2.3	imes10^{0}$     | Own calculations based on plant<br>owner's data                     | Lubricating oil production  |  |
| Direct emissions                             |                      |   |   |  |
| Carbon dioxide biogenic-AD (kg/d)            | $1.2 	imes 10^1$     | Own calculations based on plant owner's data and literature data    | Elementary flows  |  |
| Carbon dioxide biogenic-Biogas treat. (kg/d) | $6.0	imes10^0$       | Own calculations based on energy system owner's and literature data | Elementary flows  |  |
| Carbon dioxidebiogenic–CHP (kg/d)            | $1.57 	imes 10^3$    | Literature data [35]  | Elementary flows  |  |
| Carbon monoxidebiogenic–CHP (kg/d)           | $9.1	imes10^{-1}$    | Literature data [35]  | Elementary flows  |  |
| Nitrous oxide–CHP (kg/d)                     | $4.7	imes10^{-1}$    | Literature data [35]  | Elementary flows  |  |
| Methane, biogenic–AD (kg/d)                  | $4.5	imes10^{0}$     | Own calculations based on plant<br>owner's data                     | Elementary flows  |  |
| Methane, biogenic–Biogas treat. (kg/d)       | $2.2 	imes 10^0$     | Own calculations based on plant<br>owner's data                     | Elementary flows  |  |
| Methane, biogenic–CHP (kg/d)                 | $4.3 	imes 10^{-1}$  | Literature data [35]  | Elementary flows  |  |
| NMVOC–CHP (kg/d)                             | $3.8 \times 10^{-2}$ | Literature data [35]  | Elementary flows  |  |
| Platinum–CHP (kg/d)                          | $1.3 \times 10^{-7}$ | Literature data [35]  | Elementary flows  |  |
| Sulfur dioxide–CHP (kg/d)                    | $4.7 	imes 10^{-1}$  | Literature data [35]  | Elementary flows  |  |
| Capital good                                 |                      |   |   |  |
| Cement-mixing tank (tons)                    | 2.8                  | Own calculations based on plant<br>owner's data                     | Concrete block, production  |  |
| Cement-AD (tons)                             | $4.8 	imes 10^2$     | Own calculations based on plant<br>owner's data                     | Concrete block, production  |  |
| Polystyrene-AD (tons)                        | $1.1 	imes 10^0$     | Own calculations based on plant<br>owner's data                     | Polystyrene foam slab for<br>perimeter insulation, production     |  |
| Steel-AD (tons)                              | $2.4 	imes 10^1$     | Own calculations based on plant<br>owner's data                     | Reinforced steel, production                                      |  |

| Life Cycle Phase          | Amount                    | Type of Data                                    | Ecoinvent 3.6 Dataset Selected<br>for LCI Modelling |
|---------------------------|---------------------------|---|---|
| Output                    |                           |   |   |
| Electrical energy (kWh/d) | $2.2\times10^{3\text{b}}$ | Own calculations based on plant<br>owner's data | -   |
| Thermal energy (kWh/d)    | $2.5 	imes 10^{3  c}$     | Own calculations based on plant<br>owner's data | -   |
| Digestate (tons/d)        | $1.5 	imes 10^1$          | Own calculations based on plant<br>owner's data | -   |

Table 4. Cont.

<sup>a</sup> Average value calculated on an annual basis; <sup>b</sup> Net value, excluded the electrical energy self-consumed; <sup>c</sup> Net value, excluded the thermal energy self-consumed.

The process temperature is maintained at 40  $^{\circ}$ C (mesophilic conditions) by means of the thermal energy recovered from the CHP through the heat recovery circuit consisting of two pumps of 4 and 0.25 kW rated power operating 24 h/day. The thermal energy required is estimated based on the amount of biomass introduced in the AD and its specific heat capacity, the difference between the temperature inside the digester and the average local temperature, and the dispersion of heat from the digester walls, foundation, and gasholder dome. The estimated thermal energy demand ranges from 499.06 kWh/day in the summer season to 1189.75 kWh/day in the winter season. The thermal energy demand is entirely satisfied by the CHP.

The AD is made of reinforced concrete and has a polystyrene external insulation. Data about the amount of construction materials are inferred from the technical design report of the AD-CHP plant. The useful lifetime of the AD plant is assumed to be 20 years [34,35].

The biogas is stored within the gasholder dome that reaches a maximum height of 5 m from the base of the digester and it is maintained at maximum volume thanks to the injection of air by means of a pumping unit (0.5 kW, operating 24 h/day) with a pressure switch control. The daily biogas production is  $1341 \text{ m}^3/\text{day}$ . Methane content represents about 50% of the biogas volume. According to the literature, biogas leakages from AD plants are considered equal to 1% of biogas produced [21,28,43]. The biogas leakages are modelled as direct emissions associated with the anaerobic digestion process. The amount of digestate produced in the AD is equal to 15.33 tons/day.

Before being fed in the CHP, the biogas is desulfurized, filtered, and dehumidified. The desulfurization process takes place inside the AD and consists of biological desulphurization by air injection into the gasholder [43]. The insufflation occurs by means of a 0.7 kW pump operating 24 h/day. The biogas dehumidification takes place in a 5 kW chiller. It is hypothesized that biogas leakage equal to 0.5% of the volume treated occurs during the biogas purification processes [44]. Biogas leakages are modelled as direct emissions associated to the biogas treatment process.

#### 2.2.3. CHP

Biogas is burnt in the CHP internal combustion engine. It is injected into the CHP though a 1.5 kW pump operating 24 h/day. The thermal and electrical energy generated are calculated based on the thermal and electrical efficiency of the engine (Table 1), the biogas entering the CHP daily (1321 m<sup>3</sup>/day) with a low heating value of about 17.64 MJ/m<sup>3</sup>. The thermal and electrical energy generated are, respectively, 3333.51 kWh/day and 2407.89 kWh/day. Considering an operational time of 330 days per year (see Section 2.1), the electrical energy potentially generated in a timeframe of 20 years is  $1.6 \times 10^7$  kWh.

Biogas leakages from the CHP engine are considered equal to 0.5% of the biogas combusted, while the emissions related to the combustion process are based on the Ecoinvent 3.6 database [35].

The Life Cycle Inventory (LCI) for the CHP plant construction and disposal are inferred from the Ecoinvent 3.6 database. Due to a lack of primary data, the emissions into the air (direct emissions) associated with the biogas combustion within CHP (operational phase) are assumed equal to those reported in Ecoinvent 3.6 for the process "Electricity,

high voltage {IT} | heat and power co-generation, biogas". The useful lifetime of the CHP plant is assumed to be 10 years [34].

Data collection and elaboration results are recapped in Table 4.

Figure 2 synthetizes the quantified input and output for each unit process included in the analysis.



Figure 2. Input and output of the energy system unit processes.

# 3. Results and Discussion

#### 3.1. Life Cycle Impact Assessment and Interpretation

The life cycle impact assessment results of the selected FU are illustrated in Table 5. The contribution of the feedstock supply, operational phase (electrical energy and lubricant oil consumption), direct emissions, and capital good to the overall impact is detailed in Figure 3.

**Table 5.** Life cycle impact assessment results referring to the FU (1 kWh of electricity generated by the energy system).

| Impact Category                        | Total                 |
|--|-----------------------|
| GWP (kgCO <sub>2eq</sub> )             | $1.06	imes 10^0$      |
| ODP (kgCFC- $11_{eq}$ )                | $3.85	imes10^{-8}$    |
| HT–nce (CTUh)                          | $5.71 	imes 10^{-8}$  |
| HT–ce (CTUh)                           | $1.12	imes10^{-8}$    |
| PM (kg PM2.5 <sub>eq</sub> )           | $1.13	imes 10^{-4}$   |
| IR–hh (kBqU <sup>235</sup> eq)         | $2.59 	imes 10^{-2}$  |
| IR–e (CTUe)                            | $9.79	imes10^{-8}$    |
| POFP (kgNMVOC <sub>eq</sub> )          | $8.21 	imes 10^{-4}$  |
| AP (mol $H^+_{eq}$ )                   | $1.54	imes10^{-3}$    |
| $EU_T$ (molN <sub>eq</sub> )           | $3.05	imes10^{-3}$    |
| $EU_{F}$ (kgP <sub>eq</sub> )          | $4.98	imes10^{-5}$    |
| $EU_M$ (kgN <sub>eq</sub> )            | $2.29 	imes 10^{-4}$  |
| E <sub>Fw</sub> (CTUe)                 | $5.44	imes10^{0}$     |
| LU (kgC <sub>deficit</sub> )           | $7.81 	imes 10^{-1}$  |
| WRD (m <sup>3</sup> <sub>water</sub> ) | $1.41 \times 10^{-3}$ |
| MFRRD (kgSb <sub>eq</sub> )            | $5.46	imes10^{-6}$    |



Figure 3. Contribution of feedstock supply, operational phase, direct emissions, and capital good.

The process contribution analysis highlights that the feedstock supply, including the transport of the different feedstocks to the plant and the "sulla" ensiling process, represents a significant share in almost all the investigated impact categories (Figure 1). Specifically, it contributes more than 50% to mineral fossil fuels and renewable depletion (64%), ozone depletion potential (53%), and land use (53%). The feedstock transport is responsible for the highest contribution. In detail, it contributes to the impact with percentages ranging from a minimum value of 2.5% (for water resource depletion) to a maximum value of 62% (for mineral fossil fuels and renewable depletion). The "Sulla" ensiling process represents a percentage lower than 0.5% in all the examined impact categories.

Concerning the transport process, deeper analysis shows that the lead and zinc used for lorry construction and maintenance phases are responsible for the highest contribution to mineral fossil fuels and renewable depletion.

This outcome is consistent with previous LCA studies on energy valorization of residual biomass [12]. Then, reducing the transport distance for residual biomass supply chain can significantly improve the environmental performance of the examined energy system. The comparison of the energy valorization of bio-wastes through an AD-CHP system with other systems is complex because of differing assumptions, in terms of both the method (e.g., functional unit, system boundary, impact categories assessment, credits for co-products, accounting for biogenic carbon contribution on GWP, etc.), feedstock in input (energy crops, residual biomasses or a mix of them), and obtained products (biogas, bio-char [45], syngas [46]). The comparison with LCA studies on an AD-CHP plant fueled with bio-wastes is carried out referring only to the GWP impact category since this is the only environmental category investigated in all the studies analyzed. The comparison highlights that the impact on GWP from the literature (about  $2.10 \times 10^{-1} \text{ kg CO}_{2eq}$  [3,34,47] is lower than the value obtained in this study (1.06 kg  $CO_{2eq}$ ). However, contrary to this study, the cited LCAs [3,34,47] do not account for CO<sub>2</sub> emissions associated with biogas combustion in the CHP since they are considered carbon neutral. There is no consensus in the scientific community on this aspect [44,48]. Considering the importance of the valorization of residual biomasses in the transition to a circular economy, the issue of climate neutrality of biogenic carbon must be investigated and regulated.

The plant operational phase includes the electrical energy consumed for mixing the biomass, and during the anaerobic digestion, biogas treatment, and energy generation (CHP) processes, and the lubricant oil consumption. The contribution of the electricity consumption to the different impact categories is relevant. It ranges from a minimum of about 13% for climate change up to 95% for water resource depletion. Moreover, it contributes percentages higher than 60% to freshwater ecotoxicity (about 80%), freshwater eutrophica-

tion (77%), and ionizing radiation on human health (63%). The highest contributions are related to the electricity consumed during the anaerobic digestion process (more than 50%). Then the transition towards an electricity mix with a high share of renewable energy source can significantly improve the environmental performance of the system examined [49].

The lubricant oil represents a contribution lower than 2% to all the examined impact categories.

Direct emissions are responsible for the highest impact in climate change (76%). In addition, they contribute about 30% to acidification potential and terrestrial eutrophication, about 25% to photochemical ozone formation potential and marine eutrophication, and 15% to particulate matter. To climate change, the larger contribution (90%) is represented by the emissions of biogenic carbon dioxide during the biogas combustion in the CHP. Biogenic CO<sub>2</sub> emissions are not considered climate neutral in the ILCD 2011 midpoint method. There is no clear consensus among scientists on the "neutrality" of biogenic carbon [48,50]. In order to highlight how this assumption affects the obtained results, in the sensitivity analysis, the impacts are evaluated with the EF 3.0 method (adapted) in which the contribution to climate change of the CO<sub>2</sub> biogenic emissions is assumed zero.

Finally, the impact of capital goods to the different impact categories is generally low, with the exception of the human toxicity–cancer effect impact category in which they contribute 20%.

Biomass transport distance and electricity consumed during the plant's operational phase are the most contributing processes to the overall life cycle impact then they are relevant parameters in the sensitivity analysis.

The LCIA results are elaborated to obtain a single score representing synthetic information of the environmental impact of the energy system examined. The normalization and weighting of the impacts are based on the EC-JRC Global, equal weighting of the ILCD 2011 Midpoint method. The environmental score in reference to the FU is 208.9  $\mu$ Pt. The contribution of each impact category is detailed in Table 6.

| Impact Category | Unit | Total                 |
|-----------------|------|-----------------------|
| GWP             | μPt  | $1.00 	imes 10^{+1}$  |
| ODP             | μPt  | $2.10 	imes 10^{-1}$  |
| HT–nce          | μPt  | $2.45 	imes 10^{+1}$  |
| HT–ce           | μPt  | $6.00 \times 10^{+1}$ |
| PM              | μPt  | $1.48	imes10^{0}$     |
| IR–hh           | μPt  | $7.15 	imes 10^{0}$   |
| POFP            | μPt  | $1.21	imes10^{0}$     |
| AP              | μPt  | $1.83	imes10^{0}$     |
| $EU_T$          | μPt  | $1.24	imes 10^{0}$    |
| $EU_F$          | μPt  | $5.08	imes10^{-1}$    |
| EU <sub>M</sub> | μPt  | $5.01 	imes 10^{-1}$  |
| $E_{FW}$        | μPt  | $9.69	imes10^{+1}$    |
| LU              | μPt  | $1.00 	imes 10^{-2}$  |
| WRD             | μPt  | $1.36	imes10^{0}$     |
| MFRRD           | μPt  | $1.89	imes10^{0}$     |

**Table 6.** Normalized life cycle impact assessment results referred to the FU (1 kWh of electricity generated by the energy system).

Data analysis highlights that the highest contribution to the environmental score is associated with the freshwater ecotoxicity (about 50%), followed by the human toxicity–cancer effect (about 29%) and the human toxicity–no cancer effect (12%).

#### 3.2. Sensitivity and Uncertainty Analysis

This section illustrates and discusses the results of the sensitivity analysis performed to assess how the methodological choices related to the multifunctionality management approach and how the selected impact assessment method affects the obtained LCIA results. Moreover, the results of Monte Carlo simulation for the uncertainty analysis of increasing/decreasing the transport distance and the electricity consumed during the operational phase by 30% is illustrated and discussed.

With reference to the LCIA method, Table 7 shows the LCIA results calculated with the EF 3.0 method (adapted) and the percentage variations with respect to those calculated with the ILCD 2011 method. Only the impact categories expressed in the same unit of measure in both EF 3.0 and ILCD 2011 methods are included in the analysis.

**Table 7.** Sensitivity analysis results—Life cycle impact assessment results in reference to the FU (EF 3.0 method/percentage variations compared to the LCIA results calculated with the ILCD 2011 method).

| Impact Category EF/ILCD                           | EF                   | Percentage Variation (EF-ILCD)/ILCD |
|---|----------------------|-------------------------------------|
| CC (kgCO <sub>2eq</sub> )                         | $3.72 	imes 10^{-1}$ | -65.0%                              |
| ODP (kgCFC- $11_{eq}$ )                           | $4.51	imes10^{-8}$   | 17.2%                               |
| IR/IR-hh (kBqU <sup>235</sup> eq)                 | $2.59	imes10^{-2}$   | 0.%                                 |
| POFP (kgNMVOC <sub>eq</sub> )                     | $8.37	imes10^{-4}$   | 2.0%                                |
| HT–nce (CTUh)                                     | $3.55	imes10^{-9}$   | -93.8%                              |
| HT-ce (CTUh)                                      | $1.06	imes10^{-10}$  | -99.0%                              |
| $AP (molH^+_{eq})$                                | $1.54	imes10^{-3}$   | 0.%                                 |
| $EU_F$ (kgP <sub>eq</sub> )                       | $4.96	imes10^{-5}$   | -0.5%                               |
| $EU_{M}$ (kgN <sub>eq</sub> )                     | $2.29	imes10^{-4}$   | 0.%                                 |
| $EU_{T}$ (molN <sub>eq</sub> )                    | $3.05	imes10^{-3}$   | -0.1%                               |
| E <sub>FW</sub> (CTUe)                            | $4.12	imes10^{0}$    | -24.2%                              |
| WRD (m <sup>3</sup> water)                        | $8.57 	imes 10^{-2}$ | 5995.1%                             |
| MFRRD/RU <sub>m&amp;m</sub> (kgSb <sub>eq</sub> ) | $4.59	imes10^{-6}$   | -15.9%                              |

The impact on climate change associated with the selected FU decreases by 65% if calculated with the EF 3.0 method. In contrast to the ILCD 2011 method, EF 3.0 assumes that biogenic  $CO_2$  emissions are climate neutral, so the impact on climate change decreases. The percentage variations are significant for human toxicity impact categories (higher than 90%) and not negligible for freshwater ecotoxicity (24%). The impact on resource consumption calculated with the EF 3.0 method decreases by about 16%, and this reduction is related to the fact that in contrast to the EF 3.0 method, the ILCD 2011 method includes the consumption of renewable energy resources (not considered within EF 3.0 method) and non-renewable energy resources (calculated with a specific indicator in the EF 3.0 method). The impact on water resource depletion is not comparable since, contrary to the EF 3.0 method, the ILCD 2011 method does not account for the water available after deducing current demand [51].

These results confirm the importance of comparing product systems providing the same function based on the LCIA results calculated with the same impact assessment method and the importance of transparency in the LCA to avoid misleading and wrong conclusions.

Concerning the multifunctionality management, Table 8 shows the environmental credits arising from avoiding the production of the mineral fertilizer displaced by the digestate and the thermal energy substituted by the surplus from the energy system examined, and the percentage reductions of the impact obtained in the expanded system compared to the reference one. The environmental credits for the avoided thermal energy and mineral fertilized production allow a reduction of the impact ranging from 10.7% (for WU) to 100% (for ODP). These results demonstrate the importance of a fully circular management of the co-products generated by productive processes. Moreover, they can be a useful support in planning sustainable agriculture practices [52].

**Table 8.** Sensitivity analysis results—Life cycle impact assessment results referred to the FU (EF 3.0 method/percentage variations compared with the LCIA results calculated with the ILCD 2011 method).

| Impact Category EF/ILCD                           | Environmental Credits<br>for Avoided Mineral<br>Fertilizer | Environmental<br>Credits for Avoided<br>Thermal Energy<br>Production | LCIA-ExS *           | Percentage Variation<br>(RS **-ExS)/ExS |
|---|--|--|----------------------|---|
| CC (kgCO <sub>2eq</sub> )                         | $-8.41	imes10^{-2}$  | $-3.96	imes10^{-1}$  | $5.85 	imes 10^{-1}$ | -45%                                    |
| ODP (kgCFC-11 <sub>eq</sub> )                     | $-3.59 	imes 10^{-9}$                                      | $-3.49	imes10^{-8}$  | $-3.38	imes10^{-11}$ | -100%                                   |
| IR/IR-hh (kBqU <sup>235</sup> eq)                 | $-2.47	imes10^{-8}$  | $-1.39	imes10^{-8}$  | $1.85	imes10^{-8}$   | -68%                                    |
| POFP (kgNMVOC <sub>eq</sub> )                     | $-2.36 	imes 10^{-9}$                                      | $-3.93	imes10^{-9}$  | $4.87	imes10^{-9}$   | -56%                                    |
| HT-nce (CTUh)                                     | $-2.94	imes10^{-5}$  | $-2.69	imes10^{-5}$  | $5.64	imes10^{-5}$   | -50%                                    |
| HT-ce (CTUh)                                      | $-2.12	imes10^{-3}$  | $-4.94	imes10^{-3}$  | $1.88 	imes 10^{-2}$ | -27%                                    |
| AP (mol $H^+_{eq}$ )                              | $-8.43	imes10^{-9}$  | $-1.55	imes10^{-8}$  | $7.40	imes10^{-8}$   | -24%                                    |
| $EU_F$ (kgP <sub>eq</sub> )                       | $-1.84	imes10^{-4}$  | $-3.96	imes10^{-4}$  | $2.40	imes10^{-4}$   | -71%                                    |
| $EU_{M}$ (kgN <sub>eq</sub> )                     | $-4.65	imes10^{-4}$  | $-4.54	imes10^{-4}$  | $6.23	imes10^{-4}$   | -60%                                    |
| EU <sub>T</sub> (molN <sub>eq</sub> )             | $-1.41 	imes 10^{-3}$                                      | $-8.85	imes10^{-4}$  | $7.54	imes10^{-4}$   | -75%                                    |
| E <sub>FW</sub> (CTUe)                            | $-1.19	imes10^{-5}$  | $-1.27	imes10^{-5}$  | $2.53 	imes 10^{-5}$ | -49%                                    |
| WRD (m <sup>3</sup> <sub>water</sub> )            | $-6.78	imes10^{-5}$  | $-8.34	imes10^{-5}$  | $7.73 	imes 10^{-5}$ | -66%                                    |
| MFRRD/RU <sub>m&amp;m</sub> (kgSb <sub>eq</sub> ) | $-1.92	imes10^{0}$   | $-1.05	imes10^{0}$   | $2.47 	imes 10^0$    | -55%                                    |

\* Expanded scenario including environmental credits from avoiding mineral fertilizer and thermal energy production; \*\* Reference scenario without environmental credits.

Table 9 presents the main results of the Monte Carlo analysis, describing the mean value, standard deviation, coefficient of variation, and 95% confidence interval (the 2.5th percentile and the 97.5th percentile).

|  | Table 9. | Uncertainty | / analysi | s results. |
|--|----------|-------------|-----------|------------|
|--|----------|-------------|-----------|------------|

| Categoria D'impatto                    | Mean<br>Value        | Standard<br>Deviation | Coefficient of<br>Variation (%) | 2.5th<br>Percentile  | 97.5th<br>Percentile |
|--|----------------------|-----------------------|---------------------------------|----------------------|----------------------|
| GWP (kgCO <sub>2eq</sub> )             | $1.07 	imes 10^0$    | $2.09 	imes 10^{-2}$  | 2.0                             | $1.03	imes 10^0$     | $1.11	imes 10^0$     |
| ODP (kgCFC-11 <sub>eq</sub> )          | $3.83	imes10^{-8}$   | $9.83	imes10^{-9}$    | 25.7                            | $2.37	imes10^{-8}$   | $6.40	imes10^{-8}$   |
| HT-nce (CTUh)                          | $5.63	imes10^{-8}$   | $4.47	imes10^{-8}$    | 79.4                            | $-2.78	imes10^{-8}$  | $1.49	imes10^{-7}$   |
| HT–ce (CTUh)                           | $1.05	imes10^{-8}$   | $5.04	imes10^{-9}$    | 47.9                            | $5.48 	imes 10^{-9}$ | $2.39	imes10^{-8}$   |
| PM (kg PM2.5 <sub>eq</sub> )           | $1.14	imes10^{-4}$   | $1.14	imes 10^{-5}$   | 10.0                            | $9.62	imes10^{-5}$   | $1.38	imes10^{-4}$   |
| IR-hh (kBq $U^{235}_{eq}$ )            | $2.56 	imes 10^{-2}$ | $1.85 	imes 10^{-2}$  | 72.0                            | $1.06	imes10^{-2}$   | $7.02 	imes 10^{-2}$ |
| IR–e (CTUe)                            | $9.76	imes10^{-8}$   | $2.80	imes10^{-8}$    | 28.6                            | $5.60	imes10^{-8}$   | $1.63	imes10^{-7}$   |
| POFP (kgNMVOC <sub>eq</sub> )          | $8.23	imes10^{-4}$   | $8.43	imes10^{-5}$    | 10.2                            | $6.94	imes10^{-4}$   | $1.02 	imes 10^{-3}$ |
| $AP (molH^+_{eq})$                     | $1.54	imes10^{-3}$   | $1.21	imes10^{-4}$    | 7.8                             | $1.34	imes10^{-3}$   | $1.80	imes10^{-3}$   |
| $EU_{T}$ (molN <sub>eq</sub> )         | $3.06 	imes 10^{-3}$ | $2.96	imes10^{-4}$    | 9.7                             | $2.54	imes10^{-3}$   | $3.70	imes10^{-3}$   |
| EU <sub>F</sub> (kgP <sub>eq</sub> )   | $5.13	imes10^{-5}$   | $2.77 	imes 10^{-5}$  | 53.9                            | $2.18	imes10^{-5}$   | $1.24	imes 10^{-4}$  |
| $EU_{M}$ (kgN <sub>eq</sub> )          | $2.29	imes10^{-4}$   | $2.48	imes10^{-5}$    | 10.8                            | $1.88	imes 10^{-4}$  | $2.87	imes10^{-4}$   |
| E <sub>FW</sub> (CTUe)                 | $5.48	imes10^{0}$    | $1.35	imes10^{0}$     | 24.7                            | $3.53	imes10^{0}$    | $8.66	imes10^0$      |
| LU (kgC <sub>deficit</sub> )           | $7.85	imes10^{-1}$   | $2.26	imes10^{-1}$    | 28.8                            | $4.63	imes10^{-1}$   | $1.31 	imes 10^0$    |
| WRD (m <sup>3</sup> <sub>water</sub> ) | $5.70	imes10^{-3}$   | $1.31	imes10^{-1}$    | 2298.7                          | $-2.76	imes10^{-1}$  | $2.19	imes10^{-1}$   |
| MFRRD (kgSb <sub>eq</sub> )            | $5.44 	imes 10^{-6}$ | $1.48 	imes 10^{-6}$  | 27.2                            | $3.44 	imes 10^{-6}$ | $8.90	imes10^{-6}$   |

The results suggest that a large degree of uncertainty is introduced into WDR, HT-nce, IR-hh,  $EU_T$ , and HT-ce. Thus, the life cycle impact assessment results for the above categories are characterized by high dispersion and are strongly influenced by the variability of the input data. Concerning the other impact categories, the coefficients of variation are lower than 50%, indicating that the distribution of the results is correctly represented by the mean value and that the results are characterized by a low dispersion.

The sensitivity analysis of the electricity consumed during the operational phase shows that the environmental impacts increase/decrease at percentages ranging from  $\pm 4\%$  (for CC) to  $\pm 29\%$  (for WRD). Finally, the sensitivity analysis shows that if the transport distance is increased/decreased by 30%, the environmental impacts increase/decrease at

percentages ranging from  $\pm 1\%$  (for WRD) to  $\pm 20\%$  (for MFRRD). So, both parameters are of high interest towards a more sustainable pathway for residual biomasses valorization.

# 4. Conclusions

In the context of increasing interest in residual biomasses in bioenergy production, the authors perform an LCA study of an anaerobic digestion-combined heat and power plant fueled with residual biomass derived from the agro-food industry sector. The energy system in analyzed considering the real operational condition of the plant in which both the surplus of thermal energy and the digestate are wasted. Moreover, an improvement scenario is analyzed in which both thermal energy and digestate are valorized as valuable products.

The study provides a wide set of environmental outcomes and identifies the hot spots of the examined technology that must be carefully considered to improve its environmental sustainability.

In particular, the LCA highlights that the feedstock transport, the electrical energy consumption, and the direct emissions occurring during the operational phase are responsible for a significant contribution to different impact categories. Specifically, feedstock transport contributes 64% to mineral fossil fuels and renewable depletion and 50% to ozone depletion potential. Then, reducing transport distance could improve the environmental performance of the examined energy system in these impact categories. The contribution of the electricity consumption to the different impact categories is generally relevant. Then, measures aimed at improving the environmental performance of the electrical energy consumed and reducing the amount required can decrease the impact in almost all the examined impact categories. Direct emissions are responsible for the highest impact in climate change (66%). In considering the relevance of this impact category to society and policy, it is paramount to implement strategies preventing the greenhouse gas from entering the atmosphere.

The study highlights that the valorization of all co-products of the energy system examined can allow significant reduction of the impacts, so in order to increase the environmental benefits related to residual biomasses valorization systems, a fully circular management approach should be implemented.

The sensitivity and uncertainty analysis shows that high variability is associated with both the impact assessment method selected and the LCI data used to model the background system, so LCA transparency is key to avoiding misleading conclusions and recommendations.

**Author Contributions:** Conceptualization, all authors; Methodology, M.A.C. and S.L.; Software, M.A.C. and S.L.; Validation, M.C., M.A.C. and F.G.; Formal analysis, M.C. and F.G.; Investigation, M.A.C. and S.L.; Resources, M.C. and F.G.; Data curation M.C. and F.G.; Writing—original draft preparation, M.A.C.; Writing—review and editing, S.L. and F.G.; Supervision, M.C. Authorship must be limited to those who have contributed substantially to the work reported. All authors have read and agreed to the published version of the manuscript.

**Funding:** The research was carried out in the framework of the project PON RI 2014–2020–ARS01\_00985 "BIOFEEDSTOCK" Development of Integrated Technology Platforms for the Valorization of Residual Biomasses funded by the National Research Program Agency (PRN) 2015–2020, Area of specialization: Energy.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Conflicts of Interest: The authors declare no conflict of interest.

# References

- 1. JCR-EC JCR for the European Commission's Knowledge Centre for Bioeconomy. *Brief on biomass for energy in the European Union;* Publications Office of the European Union: Luxembourg, 2019; pp. 1–8. [CrossRef]
- Scarlat, N.; Dallemand, J.; Taylor, N.; Banja, M. Brief on Biomass for Energy in the European Union. Sanchez Lopez, J., Avraamides, M., Eds.; Publications Office of the European Union: Luxembourg, 2019. Available online: https://publications.jrc. ec.europa.eu/repository/handle/JRC109354 (accessed on 2 September 2021).
- 3. Lijó, L.; González-García, S.; Bacenetti, J.; Moreira, M.T. The environmental effect of substituting energy crops for food waste as feedstock for biogas production. *Energy* **2017**, *137*, 1130–1143. [CrossRef]
- 4. Wu, Y.; Zhao, F.; Liu, S.; Wang, L.; Qiu, L.; Alexandrov, G.; Jothiprakash, V. Bioenergy production and environmental impacts. *Geosci. Lett.* **2018**, *5*, 14. [CrossRef]
- 5. Wang, Z.; Bui, Q.; Zhang, B.; Pham, T.L.H. Biomass energy production and its impacts on the ecological footprint: An investigation of the G7 countries. *Sci. Total Environ.* **2020**, *743*, 140741. [CrossRef] [PubMed]
- 6. FAO The Water-Energy-Food Nexus. A New Approach in Support of Food Security and Sustainable Agriculture. 2014. Available online: http://www.fao.org/policy-support/tools-and-publications/resources-details/zh/c/421718/ (accessed on 2 September 2021).
- Bhatia, S.C. Advanced Renewable Energy Systems: Two Volume Set, 1st ed.; Woodhead Publishing India: New Delhi, India, 2014; ISBN 9781782422693.
- 8. Assunção, L.R.C.; Mendes, P.A.S.; Matos, S.; Borschiver, S. Technology roadmap of renewable natural gas: Identifying trends for research and development to improve biogas upgrading technology management. *Appl. Energy* **2021**, *292*, 116849. [CrossRef]
- 9. Ghorbani, B.; Ebrahimi, A.; Ziabasharhagh, M. Thermodynamic and economic evaluation of biomethane and carbon dioxide liquefaction process in a hybridized system of biogas upgrading process and mixed fluid cascade liquefaction cycle. *Process Saf. Environ. Prot.* **2021**, *151*, 222–243. [CrossRef]
- 10. Aryal, N.; Kvist, T. Alternative of biogas injection into the Danish gas grid system—A study from demand perspective. *ChemEngineering* **2018**, *2*, 43. [CrossRef]
- 11. International Energy Agency Outlook for Biogas and Biomethane. Prospects for Organic Growth, IEA, Paris. 2020. Available online: https://www.iea.org/reports/outlook-for-biogas-and-biomethane-prospects-for-organic-growth (accessed on 2 September 2021).
- 12. Bacenetti, J.; Sala, C.; Fusi, A.; Fiala, M. Agricultural anaerobic digestion plants: What LCA studies pointed out and what can be done to make them more environmentally sustainable. *Appl. Energy* **2016**, *179*, 669–686. [CrossRef]
- 13. Sala, S.; Reale, F.; Cristóbal-García, J.; Marelli, L.; Rana, P. *Life Cycle Assessment for the Impact Assessment of Policies, EUR 28380 EN*; Publications Office of the European Union: Luxembourg, 2016; Volume 28380, Available online: https://publications.jrc.ec. europa.eu/repository/handle/JRC105145 (accessed on 2 September 2021).
- 14. Zimek, M.; Schober, A.; Mair, C.; Baumgartner, R.J.; Stern, T.; Füllsack, M. The third wave of LCA as the "decade of consolidation". *Sustainability* **2019**, *11*, 3283. [CrossRef]
- 15. Fauzi, R.T.; Lavoie, P.; Sorelli, L.; Heidari, M.D.; Amor, B. Exploring the current challenges and opportunities of Life Cycle Sustainability Assessment. *Sustainability* **2019**, *11*, 636. [CrossRef]
- 16. ISO EN ISO 14040:2006/A1:2020. Environmental Management—Life Cycle Assessment—Principles and Framework—Amendment 1 (ISO 14040:2006/Amd 1:2020). 2020. Available online: https://www.iso.org/standard/76121.html) (accessed on 2 September 2021).
- ISO EN ISO 14044:2006/A2:2020. Environmental Management—Life Cycle Assessment—Requirements and Guidelines Amendment 2 (ISO 14044:2006/Amd 2:2020). 2020. Available online: https://www.iso.org/standard/76122.html) (accessed on 2 September 2021).
- 18. Fantin, V.; Giuliano, A.; Manfredi, M.; Ottaviano, G.; Stefanova, M.; Masoni, P. Environmental assessment of electricity generation from an Italian anaerobic digestion plant. *Biomass Bioenergy* **2015**, *83*, 422–435. [CrossRef]
- 19. Wang, Q.L.; Li, W.; Gao, X.; Li, S.J. Life cycle assessment on biogas production from straw and its sensitivity analysis. *Bioresour. Technol.* **2016**, *201*, 208–214. [CrossRef]
- 20. Ingrao, C.; Rana, R.; Tricase, C.; Lombardi, M. Application of Carbon Footprint to an agro-biogas supply chain in Southern Italy. *Appl. Energy* **2015**, *149*, 75–88. [CrossRef]
- 21. Bacenetti, J.; Negri, M.; Fiala, M.; González-García, S. Anaerobic digestion of different feedstocks: Impact on energetic and environmental balances of biogas process. *Sci. Total Environ.* **2013**, 463–464, 541–551. [CrossRef] [PubMed]
- 22. Rana, R.; Ingrao, C.; Lombardi, M.; Tricase, C. Greenhouse gas emissions of an agro-biogas energy system: Estimation under the Renewable Energy Directive. *Sci. Total Environ.* **2016**, *550*, 1182–1195. [CrossRef]
- Cusenza, M.A.; Longo, S.; Guarino, F.; Cellura, M. Energy and environmental assessment of residual bio-wastes management strategies. J. Clean. Prod. 2021, 285, 124815. [CrossRef]
- 24. Boulamanti, A.K.; Donida Maglio, S.; Giuntoli, J.; Agostini, A. Influence of different practices on biogas sustainability. *Biomass Bioenergy* 2013, 53, 149–161. [CrossRef]
- 25. Rehl, T.; Lansche, J.; Müller, J. Life cycle assessment of energy generation from biogas Attributional vs. consequential approach. *Renew. Sustain. Energy Rev.* **2012**, *16*, 3766–3775. [CrossRef]
- 26. Poeschl, M.; Ward, S.; Owende, P. Environmental impacts of biogas deployment Part II: Life Cycle Assessment of multiple production and utilization pathways. *J. Clean. Prod.* 2012, 24, 184–201. [CrossRef]

- Tufvesson, L.M.; Lantz, M.; Börjesson, P. Environmental performance of biogas produced from industrial residues including competition with animal feed—Life-cycle calculations according to different methodologies and standards. *J. Clean. Prod.* 2013, *53*, 214–223. [CrossRef]
- Dressler, D.; Loewen, A.; Nelles, M. Life cycle assessment of the supply and use of bioenergy: Impact of regional factors on biogas production. *Int. J. Life Cycle Assess.* 2012, 17, 1104–1115. [CrossRef]
- Styles, D.; Gibbons, J.; Williams, A.P.; Stichnothe, H.; Chadwick, D.R.; Healey, J.R. Cattle feed or bioenergy? Consequential life cycle assessment of biogas feedstock options on dairy farms. *GCB Bioenergy* 2015, 7, 1034–1049. [CrossRef]
- 30. Börjesson, P.; Berglund, M. Environmental systems analysis of biogas systems-Part II: The environmental impact of replacing various reference systems. *Biomass Bioenergy* **2007**, *31*, 326–344. [CrossRef]
- Awasthi, M.K.; Sarsaiya, S.; Wainaina, S.; Rajendran, K.; Awasthi, S.K.; Liu, T.; Duan, Y.; Jain, A.; Sindhu, R.; Binod, P.; et al. Techno-economics and life-cycle assessment of biological and thermochemical treatment of bio-waste. *Renew. Sustain. Energy Rev.* 2021, 144, 110837. [CrossRef]
- European Commission—Joint Research Centre—Institute for Environment and Sustainability. International Reference Life Cycle Data System (ILCD) Handbook—General guide for Life Cycle Assessment—Detailed guidance. First edition 10. EUR 24708 EN; Publications Office of the European Union: Luxembourg, 20 March 2010; ISBN 978-92-79-19092-6.
- NNFCC Biocentre The Official Information Portal on Anaerobic Digestion. Digestate. Available online: http://www.biogas-info. co.uk/about/digestate/ (accessed on 27 July 2021).
- 34. Fusi, A.; Bacenetti, J.; Fiala, M.; Azapagic, A. Life cycle environmental impacts of electricity from biogas produced by anaerobic digestion. *Front. Bioeng. Biotechnol.* **2016**, *4*, 26. [CrossRef] [PubMed]
- 35. Wernet, G.; Bauer, C.; Steubing, B.; Reinhard, J.; Moreno-Ruiz, E.; Weidema, B. The ecoinvent database version 3 (part I): Overview and methodology. *Int. J. Life Cycle Assess.* 2016, 21, 1218–1230. [CrossRef]
- European Commission—Joint Research Centre Institute for Environment and Sustainability. Characterisation Factors of the ILCD Recommended Life Cycle Impact Assessment Methods. EUR 25167. 2012. Available online: https://eplca.jrc.ec.europa.eu (accessed on 2 September 2021).
- Fazio, S.; Castellani, V.; Sala, S.; Schau, E.; Secchi, M.; Zampori, L. Supporting information to the characterisation factors of recommended EF Life Cycle Impact Assessment methods, EUR 28888 EN, European Commission, Ispra. 2018. Available online: https://eplca.jrc.ec.europa.eu (accessed on 2 September 2021).
- 38. Guo, M.; Murphy, R.J. LCA data quality: Sensitivity and uncertainty analysis. *Sci. Total Environ.* **2012**, 435–436, 230–243. [CrossRef]
- 39. Heijungs, R. On the number of Monte Carlo runs in comparative probabilistic LCA. *Int. J. Life Cycle Assess.* **2020**, *25*, 394–402. [CrossRef]
- 40. Longo, S.; Antonucci, V.; Cellura, M.; Ferraro, M. Life cycle assessment of storage systems: The case study of a sodium/nickel chloride battery. J. Clean. Prod. 2014, 85, 337–346. [CrossRef]
- Fusi, A.; Guidetti, R.; Azapagic, A. Evaluation of environmental impacts in the catering sector: The case of pasta. *J. Clean. Prod.* 2016, 132, 146–160. [CrossRef]
- 42. Bacenetti, J.; Fusi, A. The environmental burdens of maize silage production: Influence of different ensiling techniques. *Anim. Feed Sci. Technol.* **2015**, *204*, 88–98. [CrossRef]
- 43. Okoro, O.V.; Sun, Z. Desulphurisation of Biogas: A Systematic Qualitative and Economic-Based Quantitative Review of Alternative Strategies. *ChemEngineering* **2019**, *3*, 76. [CrossRef]
- European Environment Agency EMEP/EEA. Air Pollutant Emission Inventory Guidebook 2016. Biological Treatment of Waste—Anaerobic Digestion at Biogas Facilities—Biogas Production. Available online: https://www.eea.europa.eu/publications/ emep-eea-guidebook-2016 (accessed on 2 September 2016).
- 45. Cusenza, M.A.; Longo, S.; Cellura, M.; Guarino, F.; Messineo, A.; Mistretta, M.; Volpe, M. Environmental assessment of a waste-to-energy practice: The pyrolysis of agro-industrial biomass residues. *Sustain. Prod. Consum.* 2021, 28, 866–876. [CrossRef]
- Briones-Hidrovo, A.; Copa, J.; Tarelho, L.A.C.; Gonçalves, C.; Pacheco da Costa, T.; Dias, A.C. Environmental and energy performance of residual forest biomass for electricity generation: Gasification vs. combustion. *J. Clean. Prod.* 2021, 289, 125680. [CrossRef]
- Whiting, A.; Azapagic, A. Life cycle environmental impacts of generating electricity and heat from biogas produced by anaerobic digestion. *Energy* 2014, 170, 181–193. [CrossRef]
- Berndes, G.; Abt, B.; Asikainen, A.; Cowie, A.; Dale, V.; Egnell, G.; Lindner, M.; Marelli, L.; Paré, D.; Pingoud, K.; et al. Forest Biomass, Carbon Neutrality and Climate Change Mitigation. *European Forest Institute*. 2016. Available online: https://efi.int/publicationsbank/forest-biomass-carbon-neutrality-and-climate-change-mitigation (accessed on 2 September 2021).
- Cusenza, M.A.; Guarino, F.; Longo, S.; Mistretta, M.; Cellura, M. Environmental assessment of 2030 electricity generation scenarios in Sicily: An integrated approach. *Renew. Energy* 2020, 160, 1148–1159. [CrossRef]
- European Commission Commission Staff Working Document—Impact Assessment—Sustainability of Bioenergy. 2016. Available online: https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CONSIL:ST\_15120\_2016\_ADD\_9&from=EN (accessed on 2 September 2021).

- 51. Boulay, A.M.; Bare, J.; Benini, L.; Berger, M.; Lathuillière, M.J.; Manzardo, A.; Margni, M.; Motoshita, M.; Núñez, M.; Pastor, A.V.; et al. The WULCA consensus characterization model for water scarcity footprints: Assessing impacts of water consumption based on available water remaining (AWARE). *Int. J. Life Cycle Assess.* **2018**, *23*, 368–378. [CrossRef]
- 52. Caputo, P.; Zagarella, F.; Cusenza, M.A.; Mistretta, M.; Cellura, M. Energy-environmental assessment of the UIA-OpenAgri case study as urban regeneration project through agriculture. *Sci. Total Environ.* **2020**, *729*, 138819. [CrossRef] [PubMed]