

Obtaining Nanostructured ZnO onto Si Coatings for Optoelectronic Applications via Eco-Friendly Chemical Preparation Routes

Mirela Petruta Suchea ^{1,2,*}, Evangelia Petromichelaki ^{3,4}, Cosmin Romanitan ², Maria Androulidaki ³,
Alexandra Manousaki ³, Zacharias Viskadourakis ³, Rabia Ikram ^{4,5}, Petronela Pascariu ^{6,*}
and George Kenanakis ^{3,*}

- ¹ Center of Materials Technology and Photonics, Hellenic Mediterranean University, 71410 Heraklion, Crete, Greece
 - ² National Institute for Research and Development in Microtechnologies (IMT-Bucharest), 023573 Bucharest, Romania; cosmin.romanitan@imt.ro
 - ³ Institute of Electronic Structure and Laser, Foundation for Research & Technology-Hellas, N. Plastira 100, 70013 Heraklion, Crete, Greece; epetromichelaki@physics.uoc.gr (E.G.P.); pyrhnas@physics.uoc.gr (M.A.); manousa@iesl.forth.gr (A.M.); zach@iesl.forth.gr (Z.V.)
 - ⁴ Physics Department, University of Crete, 71003 Heraklion, Greece; raab@um.edu.my
 - ⁵ Department of Chemical Engineering, University of Malaya, 50603, Kuala Lumpur, Malaysia; raab@um.edu.my (R.I.)
 - ⁶ "Petru Poni" Institute of Macromolecular Chemistry, 700487 Iasi, Romania
- * Correspondence: mirasuchea@hmu.gr or mira.suchea@imt.ro (M.S.); dorneanu.petronela@icmpp.ro (P.P.); gkenanak@iesl.forth.gr (G.K.)




Figure S1. Williamson-Hall plot (red line) for the synthesized samples from Zn powder & Hexamethylenetetramine (HMTA) – column 1, Zn powder & baking ammonia – column 2 and Zn powder at 195°C in water, ethanol, soda water, lemon beverage and hydrogen peroxide, respectively - column 3. The value of the intercept and slope, as well as the fitting parameter R^2 , that shows the goodness of fit are listed in each case.