

Supplementary Materials

In Situ Grown Mesoporous Structure of Fe-Dopant@NiCoO_x@NF Nanoneedles as an Efficient Supercapacitor Electrode Material

Yedluri Anil Kumar ^{1,2,†}, Ganesh Koyyada ^{3,†}, Dasha Kumar Kulurumotlakatla ⁴, Jae Hong Kim ³, Md Moniruzzaman ^{5,*}, Salem Alzahmi ^{1,2,*} and Ihab M. Obaidat ^{2,6,*}

- ¹ Department of Chemical & Petroleum Engineering, United Arab Emirates University, Al Ain-15551, United Arab Emirates; yedluri.anil@gmail.com
² National Water and Energy Center, United Arab Emirates University, Al Ain 15551, United Arab Emirates
³ Department of Chemical Engineering, Yeungnam University, 214-1, Daehak-ro 280, Gyeongsan 712-749, Gyeongbuk-do, Republic of Korea; ganeshkoyyada@gmail.com (G.K.); jaehkim@ynu.ac.kr (J.H.K.)
⁴ Graduate School of Convergence Science, Pusan National University, San 30 Jangjeon-dong, Geumjeong-gu, Busan 609-735, Republic of Korea; dashakumar1212@gmail.com
⁵ Department of Chemical and Biological Engineering, Gachon University, 1342 Seongnam-daero, Seongnam-si, Gyeonggi-do 13120, Republic of Korea
⁶ Department of Physics, United Arab Emirates University, Al Ain 15551, United Arab Emirates
* Correspondence: mani57chem@gachon.ac.kr (M.M.); s.alzahmi@uaeu.ac.ae (S.A.); iobaidat@uaeu.ac.ae (I.M.O.)
† These authors contributed equally to this work.




Figure S1. Electrochemical characteristic of the as-synthesized electrodes at a three-electrode system: (a) Full CV tests for NiCoO_x@NF nanowires electrode at several applied scan rates, and (b) Full GCD tests for NiCoO_x@NF nanowires electrode at several applied currents.