

Supplementary Materials: Superstrate Structured FTO/TiO₂/In₂S₃/Cu₂ZnSnS₄ Solar Cells Fabricated by a Spray Method with Aqueous Solutions

Dongho Lee ^{1,2} and JungYup Yang ^{3,*}

¹ PV Development Team, Energy Solution Business Division, Samsung SDI, Cheonan-si 30186, Korea; dhlee0333@gmail.com

² Department of Electrical Engineering, State University of New York at Buffalo, Buffalo, NY 14260, USA

³ Department of Physics, Kunsan National University, Gunsan-si 54150, Korea

* Correspondence: jungyup.yang@kunsan.ac.kr

Received: 17 May 2020; Accepted: 5 June 2020; Published: 7 June 2020




Figure S1: TiO₂ thickness vs. concentration of TAA solution. Thickness is extracted from the SEM measured results on FTO (temperature 450 °C, pressure 10 psi, spray 40 cycles).




Figure S2: In₂S₃ thickness vs. the number of spraying cycles. Thickness is extracted from the scanning electron microscopy (SEM) measured results on FTO (temperature 350 °C, solution InCl₄ (12 mM) + thiourea (80 mM), pressure 6 psi).



© 2020 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).