

Electrospinning Chitosan/Fe-Mn Nanofibrous Composite for Efficient and Rapid Removal of Arsenite from Water

**Lingli Min¹, Yahui Ma¹, Bi Zhang¹, Dulan He¹, Jinhua Chen¹, Xuerong Li¹, Shuhua Wang¹
and Yulang Chi^{2,*}**

¹ College of Resources and Environmental Science, Quanzhou Normal University,
Quanzhou 362000, China

² College of Oceanology and Food Science, Quanzhou Normal University,
Quanzhou 362000, China

* Corresponding author. College of Oceanology and Food Science, Quanzhou Normal University,
398 Donghai Road, Quanzhou 362000, China

E-mail address: ylchi@qztc.edu.cn (Y. Chi).

Supplementary data

Table S1. Concentration of the dissolved ions in the natural groundwater sample. (Unit: mg/L)

As	Fe	Cu	Zn	Cr	Pb
0.00035	0.00112	0.00012	0.00186	0.00011	0.00033
F	Cl ⁻	SO ₄ ²⁻	NO ₃ ⁻	PO ₄ ³⁻	F ⁻
0.517	53.4	69.5	12.1	0.065	0.517

Table S2. Binding energies and relative contents of C and O in the fresh and As(III)-loaded biosorbent.

Valence state	Sample	Assignment	Binding energy (eV)	Relative Content (%)
C 1s	Fe-Mn@CS	C–C/C–H	284.8	26.9%
		C–O/C–N	286.4	57.6%
		C=O/O–C–O	288.0	15.5%
	Fe-Mn@CS-As	C–C/C–H	284.8	28.8%
		C–O/C–N	286.3	51.3%
		C=O/O–C–O	287.8	19.9%
O 1s	Fe-Mn@CS	M–O	529.7	5.3%
		–OH	532.4	46.0%
		H ₂ O	532.8	48.7%
	Fe-Mn@CS-As	M–O	530.0	6.3%
		–OH	532.2	37.8%
		H ₂ O	532.7	55.9%