

Mechanically robust dual-crosslinking elastomer enabled by a facile self-crosslinking approach

Zhendong Huang^a, Biqiang Jin^a, Haitao Wu^a, Zihang Zeng^a, Minghui Huang^a, Jinrong Wu^a, Lusheng Liao^{b*}, and Jing Zheng^{a*}

^a State Key Laboratory of Polymer Materials Engineering, College of Polymer Science and Engineering, Sichuan University, Chengdu 610065, China

^b Guangdong Provincial Key Laboratory of Nature Rubber Processing, Agricultural Products Processing Research Institute of Chinese Academy of Tropical Agricultural Science, Zhanjiang 524001, China

Corresponding author contact:

Associate Professor Jing Zheng

State Key Laboratory of Polymer Materials Engineering, College of Polymer Science and Engineering, Sichuan University, Chengdu 610065, China

Email: zhengjing@scu.edu.cn

Professor Lusheng Liao

Guangdong Provincial Key Laboratory of Nature Rubber Processing, Agricultural Products Processing Research Institute of Chinese Academy of Tropical Agricultural Science, Zhanjiang 524001, China

Email: 276491692@qq.com

Supplementary data




Figure S1. DSC curves of SCDCEs samples under N₂ in the temperature range of -70 °C to 60 °C at a heating scan rate of 5 °C min⁻¹.




Figure S2. Recovery time of SCDNE-0.8 after stretched to the strain of 300%.